

EQUINE OT REQUIREMENT

Sr.No	PRODUCT - DESCRIPTION:	UNIT	QTY	RATE
1	SS SWING DOOR standard size with Installation	NOS	1	
	DOUBLE shutter door with double glaze view glass all fitting in SS and with Gasket on all four sides for air sealing - SS 304 grade 1.6mm thicksheet twin sheet infill of honeycomb. Viewing Window 300 x 300mm and for smooth effortless sliding			
2	SS SWING DOOR standard size with Installation	NOS	1	
	SINGLE shutter door with double glaze view glass all fitting in SS and with Gasket on all four sides for air sealing - SS 304 grade 1.6mm thicksheet twin sheet infill of honeycomb.			
3	MANUAL - SURGICAL SCRUB SINK DOUBLE BAY (ELBOW & FOOT Operated) with Installation	NOS	1	
	Compact Surgical Sink 2 - Bay made out of SS 304 Stainless Steel Seamless Welding, Polished to stain finish complete, Strainers, Jaquar Spouts & manual foot operated bypass system etc. (L-145Cm x W-54 x H 84Cm)			
5	OT FLOORING & WALLS			
	The internal walls and floor surfaces, must be of such a nature that they can be properly cleaned and disinfected so as to maintain optimum hygienic conditions.			
a	Floor Area	SQFT	504	
b	5' Ht wall area	SQFT	385	
6	PERIFERRAL LIGHTS (LED 1ft x 1ft)	NOS	14	
7	ELECTRICAL CABLING & POINTS	NOS	15	
8	AIR CONDITIONING (2 TON)	NOS	2	
9	ANESTHESIA & RECOVERY ROOM PADING			
	Padded with a material that is impervious and can be easily cleansed and disinfected, and which covers the whole floor area as well as the wall to a height of at least two metres.			
a	Floor Area	SQFT	416	
b	8' ft Wall Area	SQFT	560	
TOTAL				

